

BUILDWELL

COARSE PUTTY

MILAYE
SIRF PAANI
LAGAYE BINA
PARESHAANI.®



30 Kg Bag | PACKAGING

Highlights

- ✓ Reduced Putty Consumption
- ✓ Reduction In Cracking
- ✓ Strong Bonding To The Base/Concrete Plaster
- ✓ Can Be Used On New As Well As Old Wall/Ceiling

HOW TO APPLY



1 Clean the surface with sand paper/wire brush & then dampen the surface.



2 Add Coarse Putty in water to obtain a lump free paste & mix well. (Recommended mix 30 - 40% water)



3 Let it stand for 10 minutes for all the additives to dissolve completely.



4 Apply 1st coat with putty blade. (Thickness of 2- 5 mm)



5 Allow the surface to dry for atleast 3-4 hours.



6 Pre wet the 1st coat need based and then apply 2nd coat.

TECHNICAL INFORMATION

TEST	TEST METHOD	SPECIFICATION	RESULTS
Whiteness	IS: 8042-1989	>70%	86.8
Chalking Resistance	Internal	No Chalking	No Chalking

PROPERTY	TYPICAL RESULTS
Pot life	60 Minutes

KEY FEATURES

- Cost-effective
- Ease of use at site
- Excellent workability
- Superior Whiteness



STORAGE

