

HOMESURE

COLOUR PUTTY

MILAYE
SIRF PAANI
LAGAYE BINA
PARESHAANI®



Highlights

- ✓ Can Save 100% Of Painting Cost
- ✓ Gives Smooth And Glossy Finish
- ✓ Can Be Applied On Interior Walls And Ceiling
- ✓ Available in 4 Colour

HOW TO APPLY



Clean the surface with sand paper / putty blade & then dampen the surface.



Add Putty in water to obtain a lump free paste & mix well. [Recommended mix 40% water]



Let it stand for 10 minutes for additives to dissolve & then Re-mix it again for 2minutes.



Apply 1st coat with putty blade. [Thickness of 0.5-1mm]



Allow the surface to dry for atleast 3-4hours.



Pre wet the 1st coat need based and then apply 2nd coat.

TECHNICAL INFORMATION

TEST	TEST METHOD	SPECIFICATION	RESULTS
Water Demand	IS:4031(Part-4)1988	30-45%	34.5
Pot Life	Internal	>90 Minutes	120
Setting Time: Initial	IS:4031 (part-5) :1988	>30 min	275-295
Setting Time: Final		<=600 min	285-300

PROPERTY	TYPICAL RESULTS
Coverage	8 - 15 Sq.Ft/Kg [Depending on finish of the Wall]
Recommended Mixing	300 - 400 ml of water per kg

KEY FEATURES

- Excellent adhesion to wall surface
- Cost-effective
- No painting required
- Aesthetic look for ceiling and interior walls



STORAGE

