

BUILDWELL

INTERNAL TEXTURE

MILAYE
SIRF PAANI
LAGAYE BINA
PARESHAANI®



30 Kg Bag | PACKAGING

Highlights

- ✓ Aesthetic Surface Finish
- ✓ Durable
- ✓ Does Not Require Curing
- ✓ Fungi Resistant

HOW TO APPLY



1 Clean the surface with sand paper/wire brush or putty blade for removing loose particles.



2 Dampen the surface with clean water and allow excess water to drain off.



3 Add texture in water to obtain a lump free paste & mix well. [Recommended mix 15 -20% water].



4 Let it stand for 10 minutes for all the additives to dissolve completely.



5 Re-Mix again for 2 minutes. Use the prepared mix within 30 minutes.



6 Apply in patches and with the help of plastic / fiber trowel move uniformly on the surface to get the desired texture pattern and uniform leveling.

TECHNICAL INFORMATION

TEST	TEST METHOD	SPECIFICATION	RESULTS
Physical Appearance		White to pale cream	White to pale cream
Drying Time (Dry to Touch)	Internal	0-1 Hour	50 min
Drying Time (Tack Free)	Internal	Max 8 Hour	5

PARAMETER	SPECIFICATION
Physical state	Ready to use dry mix powder
Appearance	White to pale cream
Pot life	60 minutes
Dry to touch @ 30Deg.	0-1 Hrs. @ 30Deg.
Tack free @ 30Deg.	Max 8 Hrs.

COVERAGE

150 to 180 sq.ft. / bag (Depending on surface of the wall)

Internal Texture (1- 1.5 mm)

KEY FEATURES

- Good workability & high durability
- It is highly compatible with plaster and concrete wall surface
- Excellent resistance against the growth of algae & fungi on the wall
- Provides best value for money
- Tough Textured



STORAGE

